



01 Screw Jack to DIN 4425

Ø 38 mm, for scaffold tubes 48,3 x 4 mm, with base plate 150 x 150 mm, with nut, SWL 50 kN, **hot-galvanized**



length of jack	mm	300	500	600	780	1000
adjustment	mm	120	320	420	600	820
weight	kg	2,60	2,82	2,96	3,74	5,20
packing	pallet/pc.	350	250	200	200	200
art.no.		01203550	01203555	02402159	01203560	02402069

02 Screw Jack Swivel Type,

Ø 38 mm x 555 mm, SWL 25,4 kN, packing unit 250 pcs. per pallet
art.no. 02402046..... 3,19 kg



03 TITAN Wedge Jack 500

adjustment: 168-268 mm, SWL 420 kN, packing unit 12 pcs. per pallet, **painted**,
art.no. 01203501..... 29,50 kg



04 Wrench SW 46, 260 mm, galvanized

art.no. 06203506..... 4,00 kg



05 TITAN Wedge Jack 1000

adjustment: 192-280 mm, SWL 1000 kN, packing unit 12 pcs. per pallet, **painted**,
art.no. 01203503..... 51,50 kg



06 Wrench SW 80, 400 mm, galvanized

art.no. 06203504..... 7,70 kg



07 Wrench with Torque Multiplier to release the wedge jack under load,

length 450 mm, ratchet and socket packed in a case
art.no. 06203507..... total weight 62,00 kg



08 Burn - Off Bearing Pad

Ø 150 mm; hole Ø 40 mm; 30 mm thick, SWL 150 kN,
art.no. 13203510..... 0,40 kg



09 Universal Beam Clamp

clamping width: 16-70 mm, SWL 3,0 kN
depth: 65 mm, SW 24, packing unit 500 pcs. per wire-mesh pallet
art.no. 06203509..... 1,77 kg



10 Clamp for Steel Beams

clamping width: 16-41 mm, SWL 2,5 kN
depth: 50 mm, SW 24
art.no. 01203505..... 1,20 kg